(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 10 June 2004 (10.06.2004)

PCT

(10) International Publication Number WO 2004/049569 A1

(51) International Patent Classification7:

H03K 7/08

(21) International Application Number:

PCT/IB2003/004890

(22) International Filing Date: 29 October 2003 (29.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02079943.3

EP 22 November 2002 (22.11.2002)

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MELS, Frank, K., I. [BE/BE]; Prof. Holstlaan 6, NL-5656 AA Eindhoven

(74) Agent: GROENENDAAL, Antonius, W., M.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

[Continued on next page]

(54) Title: PWM GENERATOR



(57) Abstract: A PWM generator (100; 200; 300; 400) is described, which does not require a separate saw-tooth generator and a separate comparator for generating a modulated pulsed signal. According to the invention, the input signal (Sin) is supplied to one input terminal (111) of a comparator (110), which receives at its other terminal (112) a feedback signal which is derived from the output signal (Sout) via an integrator device (150), in such a way that the circuit is self-oscillating. The feedback signal is a sloping signal. The comparator switches its output when the feedback signal crosses the level of the input signal, which in turn causes the feedback signal to invert its slope. Thus, the feedback signal in effect provides a saw-tooth signal without being generated by a separate saw-tooth generator.